



US009637064B1

(12) **United States Patent**
Kuehnle et al.

(10) **Patent No.:** **US 9,637,064 B1**
(45) **Date of Patent:** **May 2, 2017**

(54) **APPARATUS AND METHOD FOR
RESTORING A CAMERA MOUNTING TO A
CALIBRATED POSITION**

(71) Applicant: **Bendix Commercial Vehicle Systems
LLC**, Elyria, OH (US)

(72) Inventors: **Andreas U Kuehnle**, Villa Park, CA
(US); **Marton G Gyori**, Budapest
(HU); **Hans M Molin**, Mission Viejo,
CA (US); **Thomas S Legeza**, Olmsted
Township, OH (US)

(73) Assignee: **Bendix Commercial Vehicle Systems
LLC**, Elyria, OH (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/882,776**

(22) Filed: **Oct. 14, 2015**

(51) **Int. Cl.**
B60R 11/04 (2006.01)
G03B 17/56 (2006.01)
H04N 5/225 (2006.01)
B60R 11/00 (2006.01)

(52) **U.S. Cl.**
CPC **B60R 11/04** (2013.01); **G03B 17/561**
(2013.01); **H04N 5/2252** (2013.01); **H04N**
5/2253 (2013.01); **B60R 2011/004** (2013.01);
B60R 2011/0059 (2013.01)

(58) **Field of Classification Search**
USPC 396/428
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,244,140 A	1/1981	Kim	
4,658,335 A	4/1987	Culler	
5,876,005 A *	3/1999	Vasconi	F16M 11/10 248/276.1
6,364,496 B1 *	4/2002	Boddy	B60R 1/072 248/476

(Continued)

FOREIGN PATENT DOCUMENTS

EP	1243793 A2	9/2002
EP	1251381 A2	10/2002

(Continued)

OTHER PUBLICATIONS

Johnson Matthey, "Nitinol Shape Setting," webpage, <http://jmmedical.com/resources/251/Nitinol-Shape-Setting.html>, printed Aug. 21, 2015, Johnson Matthey Medical Components.

(Continued)

Primary Examiner — Clayton E LaBalle

Assistant Examiner — Linda B Smith

(74) *Attorney, Agent, or Firm* — Cheryl L. Greenly; Brian
E. Kondas; Eugene E. Clair

(57) **ABSTRACT**

Various examples of an apparatus for mounting a camera on a vehicle are disclosed. An apparatus comprises a first portion of a first material with a first end configured for attaching to a camera and a second end configured for mounting to a vehicle. The apparatus is configured to maintain the camera in a substantially calibrated position. A second portion of a second material is coupled to the first portion, wherein the second material is capable of deforming

(Continued)

